MATERIAL SAFETY DATA SHEET

PRODUCT/MATERIAL Glassline

MANUFACTURER/DISTRIBTOR Clay Art Center

ADDRESS: 2636 Pioneer Way East Tacoma WA. 98404

PHONE/FAX 253 922-5342 Fax 253 922-5349

SECTION 1-PRODUCT INFORMATION

Glassline TRADE NAME: SYNONYM: Glassline Gold CHEMICAL FAMILY: Ceramic Glaze

SECTION 11-HAZARDOUS INGREDIENTS

Maximum		n	OSHA PEL	NIOSH REL	ACGIH TLV
INGREDIENT NAME	Percent	CAS NUMBER	TWA: (mg/m3)	TWA: (mg/m3)	TWA: (mg/m3)
			-	_	_
Fluorides,as F	2	7789-75-5	2.5		2.5
Silica, Crystalline (Quartz)	2	14808-60-7	10 mg/m3/%SiO2 +2		
Mica (mineral)	4	12001-26-2	3 mg/m3	3 mg/m3	3 mg/m3

SECTION 111-PHYSICAL DATA

BOILING POINT Not Applicable VAPOR PRESSURE Not Applicable VAPOR DENSITY Not Applicable SOLUBILTY IN WATER Insoluble SPECIFIC GRAVITY 1.7 - 3.7PERCENT SOLUBLE BY WEIGHT 0 **EVAPORATION RATE** APPEARANCE AND COLOR Gold; no odor

SECTION 1V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT Not Flammable

EXTIGUISING MEDIA Water UNUSUAL FIRE OR EXPLOSION HAZARDS None SPECIAL FIRE FIGHTING PROCEDURES None

SECTION V - REACTIVITY DATA

STABILITY FACTOR Product is stable

INCOMPATIBILITY None

HAZARDOUS DECOMPOSITION PRODUCTS None Hazardous polymerization will not occur

CONDITIONS TO AVOID Inhalation of dust

SECTION V1 - HEALTH HAZARD DATA

Fluoride containing vapors from firing may cause lung inflamation and injury in terms of hours with symptoms of chestpains, cough, headache, and diarrhea. Prolonged contact with dust can be very irritating to the eyes and or skin. High levels can be irritating to the respiratory tract. With adequate ventilation, dust control, and personal hygiene, symptoms of over exposure should not occur.

Silica, Crystalline (Quartz) A single exposure will not result in serious adverse health effects. Respirable crystalline silica (quartz) can cause silicosis, a fibros (scarring) of the lungs. Silicosis may be progressive; it may lead to disabilty and death. Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans. There are some studies that show excess numbers of cases of scleroderma and other connective tissue disorders in workers exposed to respirable crystalline silica. Silicosis increases the risk of tuberculosis. There are some studies that show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Copper or Copper Compounds - Overexposure can cause nausea, chills, diarrhea. May cause respiratory irritation, skin irritation (oxide pox), fever, eye irritation with redness, pain, and conjunctivitis; preexisting lung diseases may be aggravated by exposure. Could result in respiratory disease if over-exposed on a chronic basis.

PRIMARY ROUTES OF ENTRY: Inhalation (Dry form only), ingestion and dermal.

SUMMARY RISKS: Individuals with a lung disease/condition (e.g.: bronchitis, emphysema, chronic

pulmonary disease can be aggravated by exposure.

EMERGENCY FIRST AID: No specific first aid is necessary since the adverse health effects associated with

this compound results from chronic exposure.

Eye Contact May be an irritant, flush eyes with generous amounts of water for at least 15

minutes: call a physcian if irritation persists.

Skin Contact May cause local dermatitis, which is relieved when removed.

Ingestion Toxicity due to ingestion is low.

Inhalation Remove to fresh air, call a physician if irritation due to inhalation persist.

Physician's Note None

SECTION V11 - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills or Release Procedure Follow normal clean-up procedures. Care should be taken to avoid causing dust to

become airborne. Vacuum or use wet clean-up techniques.

Waste Disposal Dispose material in accordance with Federal, State, and Local regulations.

SECTION V111 - CONTROL MEASURES

Provide adequate ventilation to keep dust or vapor concentrations below acceptable exposure limits. Use gloves as needed for habdling material containers. Wear safety glasses when needed. Appropriate respiratory protection may be required to protect from certain dusts. Respirators must be selected and used in accordance with OSHA Subpart 1 of (29 CFR 1910.134).

SECTION 1X - TOXICOLOGICAL INFORMATION

This product (and all of it's componets) is in compliance with the U.S. EPA 15 U.S. C.2604 regulation. This product is certified as NON-TOXIC, and conforms to ASTMD-4236 and C-1023 under the federal Labeling of Hazardous Art Materials Act (LHAMA).

SECTION X - REGULATORY

This product may contain materials that are reportable under Section 313 of the Emergency Planning and Community Right -To-Know Act (Superfund Amendments and Reauthorization Act - SARA), and 40 CFR Part 372.

SARA Title 111 Data: These levels are "typical quanties" and may change slightly with different lots.

This product contains substances regulated under California's safe drinking water and toxic enforcement act (proposition 65)

SECTION X1 - DISCLAIMER

The information provided in this MSDS document has been provided to Clay Art Center by its material suppliers and is represented by those suppliers as accurate and reliable.

Clay Art Center is not liable for injury, loss, or damage, direct or consequential, arising out of the use or inability to properly use this product. This product is intended for use in traditional glass applications.

This MSDS conforms to the ASTM D-4236 and C-1023 requirements defined by LHAMAS, the Federal Labeling of Hazardous Art MaterialsAct. LHAMA was developed by the American Society of Testing and Materials (ASTM) to ensure the proper labeling of art materials.